

VIBRATION MEASUREMENT

VIBRATION ANALYZER

PCE-VT 3900 / PCE-VT 3900S

Vibration analyzer with internal memory / route measurement

The vibration analyzer is an ideal measuring device for fast and precise checking of vibrating parts, machines and systems. This vibration meter uses the external vibration sensor to determine the vibration displacement (measuring range 0.000 ... 3.9 mm), the vibration velocity (measuring range 0.00 ... 399.9 mm/s) and the vibration acceleration (measuring range 0.0 ... 399.9 m/s²). Various measure-

ment parameters are available for the vibration meter, such as RMS, peak, peak-peak and crest factor. The vibration meter is equipped with a mode that allows a measurement to be automatically evaluated according to the limit values of ISO 10816-3.

ISO cal option

- » for mobile vibration measurement
- » measuring range up to 399.9 m/s² / 15744 in/s²
- » FFT analysis
- » route measurement
- » manual measured value memory
- » automatic ISO 10816-3 evaluation
- » internal memory
- » 2.48" LC display



APPLICATION



TECHNICAL SPECIFICATIONS

Measuring range	Acceleration 0.0 ... 399.9 m/s ² / 0.0 - 15744 in/s ²	Sensor PCE-VT 3900	Sensor with spiral cable PCE-VT 3xxx SENSOR
Resolution	0.1 m/s ² / 3.94 in/s ²	Magnet adapter PCE-VT VMH	Magnet adapter PCE-VT VMH
Accuracy @ 160 Hz	±2 %	Sensor PCE-VT 3900S	Sensor with spiral cable PCE-VT 3xxx SENSOR
Frequency range	10 Hz ... 10 kHz	Needle sensor PCE-VT NP	Needle sensor PCE-VT NP
	1 kHz ... 10 kHz	Handle PCE-VT 3xxx HANDLE	Handle PCE-VT 3xxx HANDLE
Measuring range	Velocity 0.00 ... 399.9 mm/s / 0.00 - 15.74 in/s	Technical Data Vibration Sensor	
Resolution	0.1 mm/s / 0.0039 in/s	Resonance frequency	24 kHz
Accuracy @ 160 Hz	±2 %	Transverse sensitivity	≤ 5 %
Frequency range	10 Hz ... 1 kHz	Destruction limit	5000 g (peak)
Measuring range	Rotational Speed 600 ... 50000 RPM	Operating and storage temperature	-55 °C ... +150 °C / -67 °F ... 302 °F
	10 Hz ... 8 kHz	Housing material	stainless steel
	10 Hz ... 1 kHz	Mounting thread	1/4 - 28"
	±2 %	Dimensions	Ø 17 x 46 mm / 0.67 x 1.8"
	2048	Weight (without cable)	52 g / 1.8 oz
FFT acceleration	Displacement 0.000 ... 3.9 mm / 0.000 - 0.154 in	Optional accessories:	
FFT velocity	1 μm / 39.4 μin	PCE-VT NP	Needle sensor
Accuracy @ 160 Hz	±2 %	PCE-VT VMH	Magnet adapter
Number of FFT lines	10 Hz ... 200 Hz	CAL-PCE-VT 3xxx	ISO Calibration Certificate
Route measurement	RMS, Peak, Peak-Peak	PCE-VT 3xxx SENSOR	replacement vibration sensor
	Crest factor		
Measuring range	99 folders with 50 measured values each	Further models:	
Resolution	Various start/stop triggers	PCE-VT 3950	incl. sensor, magnetic adapter, headset
Accuracy @ 160 Hz	Measurement interval	PCE-VT 3950S	incl. needle sensor with handgrip, headset
Frequency range	between 1 s ... 12 h		
Measurement parameters	50 memory locations with 43.200 measured values each		
Manual memory	can be switched to metric / imperial		
Data logger	2.48" LC display		
Units	English, German, French, Spanish, Italian, Dutch, Portuguese, Turkish, Polish, Russian, Chinese, Japanese		
Display	internal: LiPo battery (3.7 V, 2500 mAh)		
Menu languages	external: USB 5 VDC, 500 mA		
Power supply	ca. 15 ... 20 h (depending on display brightness)		
Operating time	temperature: -20 ... +65 °C / -4 ... 149 °F		
Operating / storage conditions	humidity: 10% RH ... 95% RH, non-condensing		
Dimensions	165 x 85 x 32 mm / 6.5 x 3.3 x 1.3"		
Weight	239 g / 8.4 oz		



Subject to change without notice